



## Model No.: OP-112 Specifications

LCD Display	12.1" TFT Active Matrix Panel
Display Size	246 x 184.5 mm
Pixel Pitch	0.264 x 0.264 mm
Display Mode	VGA 640x350 (70Hz) VGA 720x400 (70Hz) VGA 640x480 (60/72/75Hz) SVGA 800x600 (60/72/75Hz) XGA 1024x768 (60/72/75Hz) Mac. 832x624 (75Hz)
Max. Resolution	1024x768
Contrast Ratio	700:1
Brightness	500 cd/m <sup>2</sup>
Response Time	35mS (Rising + Falling)
Display Colors	16M (dithering)
Viewing Angle	+80° ~ -80°(L/R), +80° ~ -80°(U/D)
Input Signal	
Video	R.G.B Analog 0.7V Peak-to-Peak
Sync	TTL Positive or Negative
Signal Connector	15Pin Mini D-sub
Front Control	Power Switch, Menu, Select (Up, Down), Adjust (+, -)
OSD	Auto-Adjustment, Contrast, Brightness, Clock, Phase, H-Position, V-Position, Color Temperature
Plug & Play	DDC1/2B
Optional	Touch Screen
Power	Universal 90-240V, 12V/36W
Dimensions	322.4 x 247 x 47.6 mm
Weight (Net)	4 Kg
Certification	FCC-B, CE

