



Model No.: OP-115 Specifications

| | |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LCD Display | 15" TFT Active Matrix Panel |
| Display Size | 304.1 x 228.1 mm |
| Pixel Pitch | 0.297 x 0.297 mm |
| Display Mode | VGA 640x350 (70Hz) VGA 720x400 (70Hz) VGA 640x480 (60/72/75Hz) SVGA 800x600 (60/72/75Hz) XGA 1024x768 (60/70/75Hz) Mac. 832x624 (75Hz) |
| Max. Resolution | 1024x768 |
| Contrast Ratio | 700 |
| Brightness | 250 cd/m² |
| Response Time | 8mS (Raising + Falling) |
| Display Colors | 16M (dithering) |
| Viewing Angle | +80⁰ ~ -80⁰(L/R), +70⁰ ~ -60⁰(U/D) |
| Input Signal | |
| Video | R.G.B Analog 0.7V Peak-to-Peak |
| Sync | TTL Positive or Negative |
| Signal Connector | |
| | 15Pin Mini D-sub |
| Front Control | Power Switch, Menu, Select (Up, Down), Adjust (+, -) |
| OSD | Auto-Adjustment, Contrast, Brightness, Clock, Phase, H-Position, V-Position, Color Temperature, Load default |
| Plug & Play | DDC1/2B |
| Optional | Touch Screen Video in: Pal/NTSC & S-video/AV connector |
| Power | Universal 90-240V, 12V/40W (max.) |
| Dimensions | 380 x 297 x 53 mm |
| Weight (Net) | 5 Kg |
| Certification | FCC-A, CE |

